




**Wide Dynamic Range
Indoor Dome Camera**



- CVC624WDR** 2.8 - 12mm auto Irls varifocal lens, black housing
- CVC624WDRW** 2.8 - 12mm auto Irls varifocal lens, white housing

Features

- Newest WDR technology allows for improved image quality in scenes consisting of both bright and dark areas
- Each pixel processed independently for improved image
- High quality image even in low light conditions
- Sharpest quality analog image
- 12VDC/24VAC dual voltage operation
- 5 year warranty



Specifications

Image Sensor	1/3" Pixim® Seawolf DPS
Resolution	690 TV Lines
Minimum Illumination	0.1 lux (sense-up x64)
Effective Pixels	758 (H) x 540 (V)
Electronic Shutter	Max. x64 (x2, x4, x8, x16, x32, x64)
Color Balance	Multiple selectable factory presets for most common situations Full manual override for special applications
Video Output	1.0Vp-p (sync. negative) termination 75 Ohm + 10%
TV System	NTSC
Scanning System	Progressive
Synchronization	Internal / External
S/N Ratio	50dB or more (AGC off)
Dynamic Range	120dB (Max.)
AGC Control	0 - 50dB
Gamma Characteristic	0.45 NTSC
Power Supply	12VDC / 24VAC (dual voltage) (power supply not included)
Power Consumption	190mA Max.
Operating Temperature	14° F - 122° F
Dimensions	3" (H) x 5.5" (Dia.)
Weight	14.08 oz.



Optional Accessories



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Rev. 1/27/12

For more information contact Speco Technologies
200 New Highway, Amityville, NY 11701 - Toll Free: 1-800-645-5516 - Fax: 631-957-9142 or 631-957-3880
www.specotech.com