

**D4CS** 4 Channel DVR with Digital Deterrent™  
**D8CS** 8 Channel DVR with Digital Deterrent™  
**D16CS** 16 Channel DVR with Digital Deterrent™

D4CS500	D8CS500	D16CS500
D4CS1TB	D8CS1TB	D16CS1TB
D4CS2TB	D8CS2TB	D16CS2TB

**Features**

View on iPhone®, iPad®, Blackberry® or Android®

EZ Setup: for quick system setup

EZ Record: quickly setup recording schedules, resolutions and recording type

EZ Copy: auto copy what you are playing onto a USB flash drive

EZ Network: for quick set-up on a network

- H.264 recording
- Recording rate up to 480FPS
- Free Speco DDNS service for use with dynamic IP addresses
- MAC® & PC compatible software Included
- POS/ATM support with text overlay and searchable database
- Simultaneous live view or playback while continuing to record, network transfer
- Text message alerts of system activity and status
- Remote monitoring, recording, playback, change system settings and camera control via network and/or internet
- Real time live display
- IR Remote control Included - Individually control up to 16 DVRs
- Multiple analytics such as museum search and advanced motion detection
- USB 2.0 port for video clip exporting
- Easy software upgrade via Network or USB Flash drive
- Configurable per channel normal and event recording frame rate & picture quality or globally via EZ record
- Full system monitoring
- Free Central Management System (Speco Central) software allows viewing of multiple DVRs on a PC
- Email notification of alarm events
- SNS communication alert via Twitter
- Per channel built-in PTZ camera protocol including Pelco D
- Automatic camera detection (Plug & Play)
- Digital Zoom in live mode and playback
- Covert camera operation provides enhanced security and administrator control
- Playback while watching live on same monitor
  - Up to 30 minutes pre-alarm recording
  - Up to 15 minutes post-alarm recording
- 3 year warranty

• Free iPhone® & iPad® apps available from iTunes®


Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.


Rev. 2/20/12



Storage from 500GB up to 2TB



D4CS



D8CS / D16CS



For the latest mobile apps  
and CMS software go to:  
[www.specotech.com/DVRApps](http://www.specotech.com/DVRApps)



- User Access: up to 10 concurrent users
- Hard drive status monitoring
- Remote upgrade
- USB mouse supported (not included)
- Multiple language on-screen menus
- Password to secure installation with configurable user authentication levels
- 2 way audio
- DVR supports static IP, DHCP, PPPoE and DDNS
- Power Consumption: 4 CH: 12W/3A  
8/16 CH: 12W/5A
- Operating Temperature: 41° F - 104° F
- Dimensions: 4 CH: 10.4\" (W) x 2\" (H) x 7.4\" (D)  
8/16 CH: 11.8\" (W) x 2.4\" (H) x 9.1\" (D)
- Weight: 4 CH: 3.75 lbs.  
8/16 CH: 5.5 lbs.



**EZ Set-Up Wizards!**  
One click wizard guides you to set up essentials of the system in a logical and easy to understand sequence.  
• Date/Time • Recording method • Recording video quality • Network

**Optional Accessory**



ER81V  
Vented Rack Shelf