



## H.264 Multi-Channel Covert Digital Video Recorder

**D4WRS** 4 Channel  
**D8WRS** 8 Channel  
**D16WRS** 16 Channel


D4WRS250	D8WRS250	D16WRS250
D4WRS500	D8WRS500	D16WRS500
D4WRS1TB	D8WRS1TB	D16WRS1TB
	D8WRS2TB	D16WRS2TB

### Features

- 4 / 8 / 16 Channel digital video recorder in covert wall mount chassis
- Networkable DVR with free DDNS server
- User Access: up to 4 concurrent users
- Easy and simple graphical user interface
- EZCopy, EZRecord and EZSearch
- Programmable recording on motion detection, sensor, schedule, continuous and manual
- Recording rate at 120FPS at D1
- H.264 video compression
- built in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- 4 channel audio recording
- Covert camera operation provides enhanced security and administrator control
- No accessible user controls
- Password to secure installation authorization
- Easy firmware upgrade by USB port or network
- Instant and convenient backup via USB Flash Drive or Network
- Simultaneous playback/record while continuing to network transfer or backup
- Remote monitoring/recording/playback/configuration/software upgrades and PTZ control via Internet
- Network accessible via SpecoTech Multi-Client Software, Internet Explorer Web-Viewer and Speco Player Mobile Viewer
- PC & MAC® compatible
- Digital watermarking
- 3 year warranty
- Free Apps with support for View on iPhone®, iPad® or Android®



For the latest mobile apps  
and CMS software go to:  
[www.specotech.com/DVRApps](http://www.specotech.com/DVRApps)



### Specifications

120FPS @ 704 x 480 (D1)

1 Internal hard drive

H.264 video compression

4 Channel audio input, 1 Channel audio output

Motion detection, sensor, schedule, continuous and manual recording

Video Outputs: 1 VGA, 1 BNC, 1 SPOT

USB 2.0 port for snapshot and video clip exporting

Multiple language on-screen menus

IR remote control included

Network software supports Static IP, DHCP and DDNS

Network hardware supports 10 / 100 / 1000Mbps

Power requirement: 12VDC @ 3A (D4WRS),  
12VDC @ 5A (D8WRS & D16WRS)  
(power supply included)

Operating Temperature: 41° F - 104° F

Dimensions: 11.5" (W) x 15" (H) x 3.5" (D)

Weight: 8.5 lbs.

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 2/22/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880  
[www.specotech.com](http://www.specotech.com)

[http://specotech.com/media/resource\\_files/0eaaed69c0c446ee31afbea35b659d09\\_\\_\\_D4WRSP\\_spec\\_sheet.pdf](http://specotech.com/media/resource_files/0eaaed69c0c446ee31afbea35b659d09___D4WRSP_spec_sheet.pdf)